



## **Concorde Battery Corporation**

2009 San Bernardino Road  
West Covina, California, USA 91790

### **RG-213**

**24 VOLT 13 Ah, VALVE REGULATED, LEAD-ACID, AIRCRAFT BATTERY**

### **DECLARATION OF DESIGN PERFORMANCE**

**TO THE REQUIREMENTS OF**

**RTCA DO-293A and IEC 60952-1**

**Applications: Engine Starting and Emergency Power**

**NOTE: Applications may not be a complete list of all applications for this battery type.**

*The data/information contained herein has been reviewed and approved for general release on the basis that this document contains no export-controlled information*

Characteristic	RTCA DO-293A IEC 60952-1	Requirement/Performance	Test Report / Reference
Description	<p>The RG-213 is a 24 volt valve regulated lead-acid aircraft battery designed for engine starting and emergency power.</p> <p>The RG-213 battery consists of twelve 2 volt cells connected in series. The cells are enclosed by a one piece plastic monoblock container and a plastic one piece top which is secured to the monoblock with an epoxy cement. The monoblock container and top are made of high-impact polypropylene. The monoblock assembly is housed within a fuse-coated aluminum container and cover. The cover is connected to the housing using high retention rivets.</p> <p>An MS3509 conforming receptacle is used. Hold downs are integrated into the aluminum housing located at the base of the front and back. A polypropylene handle assembly for lifting the battery is fitted around the cover. Vent tubes are integrated into both the cover and the container.</p> <p>The electrolyte is a sulfuric acid and water solution and is absorbed within the battery plates and separators. There is no free electrolyte.</p>		
Format	IEC 60952-2	Concorde Drawing No. RG-213	
Connector	IEC 60952-2	The battery is available with a Type Q terminal conforming to MS-3509.	
Mass		15.0 kg Max (33 lbs).	
Charging method	IEC 60952-1, 4.3	Constant potential at 28.25 V	
Any auxiliary requirement:		None	
Ventilation	DO-293A, 1.9 IEC 60952-2	Battery is equipped with vent tubes.	
Flammability	IEC 60952-2	RG-213 outer container is fire resistant.	
Spillability		Non spill	
<b>Electrical Performance</b>			
Rated Capacity (C1)	DO-293A, 2.2.2 IEC 60952-1, 5.1.1	13 Ah	
Capacity at -18°C	DO-293A, 2.2.3 IEC 60952-1, 5.1.2	10.5 Ah when discharged at the C <sub>1</sub> rate.	
Capacity at -30°C	DO-293A, 2.2.4 IEC 60952-1, 5.1.3	7.0 Ah when discharged at the C <sub>1</sub> rate.	
Capacity at +50°C	DO-293A, 2.2.5 IEC 60952-1, 5.1.4	13 Ah when discharged at the C <sub>1</sub> rate.	
Power Rating +23°C	DO-293A, 2.2.6.1 IEC 60952-1, 5.2.1.1	I <sub>pp</sub> = 950 A, I <sub>pr</sub> = 625 A	
Power Rating -18°C	DO-293A, 2.2.6.2 IEC 60952-1, 5.2.1.2	I <sub>pp</sub> = 625 A, I <sub>pr</sub> = 400 A	
Power Rating -30°C	DO-293A, 2.2.6.3 IEC 60952-1, 5.2.1.3	I <sub>pp</sub> = 425 A, I <sub>pr</sub> = 275 A	

Characteristic	RTCA DO-293A IEC 60952-1	Requirement/Performance	Test Report / Reference
Rapid Discharge Capacity at 23°C	DO-293A, 2.3.1 IEC 60952-1, 5.3.1	6.5 Ah when discharged at 10 times the C <sub>1</sub> rate to 10 volts.	
Rapid Discharge Capacity at -30°C	DO-293A, 2.3.2 IEC 60952-1, 5.3.2	3.0 Ah when discharged at 10 times the C <sub>1</sub> rate to 10 volts.	
Charge Retention	DO-293A, 2.4 IEC 60952-1, 5.4	+23/C - Rating value for design = 80 %	
		+50/C - Rating value for design = 75 %	
Storage	DO-293A, 2.5 IEC 60952-1, 5.5	DO-293A -1 year storage life test successfully completed on the RG-400E/13.	
Charge Stability	DO-293A, 2.6 IEC 60952-1, 5.6, Class I	OK. Max battery temperature on charge = 51°C. Charge current fell during the charge period. Capacity at end of test > C1	
Short-circuit Current	DO-293A, 2.7 IEC 60952-1, 5.7	Peak current = 1940A Last recorded current = 515A at 8.6s	
Charge Acceptance	DO-293A, 2.8 IEC 60952-1, 5.8	+23/C = 100%	
		-18/C, Not Applicable	
		-40/C, Not Applicable	
Insulation Resistance	DO-293A, 2.9.1 IEC 60952-1, 5.9.1	All samples successfully met the test requirements.	
Dielectric Strength	DO-293A, 2.9.2 IEC 60952-1, 5.9.2	All samples successfully met the test requirements.	
Duty Cycle Performance	DO-293A, 2.10 IEC 60952-1, 5.10	100 cycles successfully completed.	
Water Consumption Test	DO-293A, 2.11 IEC 60952-1, 5.11	N/A	
Overcharge Endurance	DO-293A, no requirement IEC 60952-1, 5.12	Not tested	
Cyclic Endurance	DO-293A, 2.12 IEC 60952-1, 5.13	100 cycles successfully completed.	
Deep Discharge	DO-293A, 2.13 IEC 60952-1, 5.14	The sample successfully met the test requirements.	
Induced Destructive Overcharge	DO-293A, 2.14 IEC 60952-1, 5.15	The sample successfully met the test requirements.	
Electrical Emissions	DO-293A, 2.15 IEC 60952-1, 5.16	N/A, Battery contains no active electronics.	
<b>Environmental Performance</b>			
Vibration	DO-293A, 3.1 IEC 60952-1, 6.1	Qualified per DO-293A to DO-160G, random vibration test per Curve C, section 8, 1 hour per axis.	
Acceleration	DO-293A, no requirement IEC 60952-1, 6.2	Not tested	

<b>Characteristic</b>	<b>RTCA DO-293A IEC 60952-1</b>	<b>Requirement/Performance</b>	<b>Test Report / Reference</b>
Operational Shock	DO-293A, 3.3.1 IEC 60952-1, 6.3, Class I	Qualified per DO-293A to DO-160G, Category B. All shock pulses were of a saw tooth configuration. Each shock pulse had an amplitude of 6g's for 11ms.	
Crash Safety Shock	DO-293A, 3.3.2 IEC 60952-1, 6.4	Qualified per DO-293A to DO-160G, Category B, impulse and sustain. Impulse shock pulses were of the saw tooth configuration. The battery was tested per DO-160G Table 7-1, Aircraft type 5, Test type R, 20g's in each orientation.	
Explosion Containment	DO-293A, 3.4 IEC 60952-1, 6.5	N/A	
Altitude	DO-293A, 3.5 IEC 60952-1, 6.6	Qualified to 20621m (67654 ft) per DO-293A.	
Rapid Decompression	DO-293A, 3.5.2 IEC 60952 no reqmt	Qualified from 2300m (8000 ft) to 20621m (67654 ft) per DO-293A.	
Temperature Shock	DO-293A, 3.6 IEC 60952-1, 6.7	Qualified per DO-293A. Temperature cycles from +85°C to -55°C.	
Fungus Resistance	DO-293A, 3.7 IEC 60952-1, 6.8	Component test. All components have been tested and qualified per DO-160G, Category F.	
Humidity	DO-293A, 3.8 IEC 60952-1, 6.9	Qualified per DO-293A to DO-160G, Category B.	

Characteristic	RTCA DO-293A IEC 60952-1	Requirement/Performance	Test Report / Reference
Fluid Contamination	DO-293A, 3.9 IEC 60952-1, 6.10	Component test. Test was performed on representative material samples. All samples successfully met the test requirements. Fluids tested: Fuels. Aviation Jet A fuel Aviation piston engine fuel (100LL AVGAS) Hydraulic fluids Mineral based (MIL-H-5606) Non-mineral based synthetic (MIL-PRF-83282 and MIL-PRF-87257) Lubricating oils Mineral based (MIL-L-6081) Ester based synthetic (MIL-L-23699) Internal combustion engine SAE 15W40 Solvents and cleaning fluids Isopropyl alcohol (TT-I-735) Denatured alcohol De-icing fluid Ethylene Glycol Propylene Glycol AMS 1424 (SAE AEA Type I) AMS 1428 (SAE AEA Type VI) Insecticides - none Sullage - none Disinfectants (heavy duty phenolics) - none Coolant dielectric fluid - none Fire extinguishants - none	
Salt Spray	DO-293A, 3.10 IEC 60952-1, 6.11	Qualified per DO-293A to DO-160G, Category S.	
Physical Integrity at High Temperature	DO-293A, 3.11 IEC 60952-1, 6.12	Qualified per DO-293A.	
Flammability	DO-293A, no requirement IEC 60952-1, 6.13	Not tested. See Section 1	
Electrolyte Resistance	DO-293A, 3.12 IEC 60952-1, 6.14	Component test. All components met the specification requirements.	
Thermal Sensors	DO-293A, 3.13 IEC 60952-1, 6.15	Not Applicable	
Component Qualification tests	DO-293A, 3.14 IEC 60952-1, 6.16	Component test. All components successfully met the performance requirements of the test.	
Battery Airtightness	DO-293A, no requirement IEC 60952-1, 6.17	N/A	

<b>Characteristic</b>	<b>RTCA DO-293A IEC 60952-1</b>	<b>Requirement/Performance</b>	<b>Test Report / Reference</b>
Cell Baffle	DO-293A, no requirement IEC 60952-1, 6.18	N/A, Applies only to nickel-cadmium batteries only.	
Strength of Receptacle	DO-293A, 3.15 IEC 60952-1, 6.19	OK	
Handle Strength	DO-293A, 3.16 IEC 60952-1, 6.20	OK	

N/A = Not Applicable

**Authentication:**

Manufacturer.

Concorde Battery Corporation

Signed:

Name of signatory:

John B. Timmons, PE

Title or Function:

Senior Vice President Engineering