



Concorde Battery Corporation

2009 San Bernardino Road
West Covina, California, USA 27106

RG-400E/13

24 VOLT 13 Ah, VALVE REGULATED, LEAD-ACID, AIRCRAFT BATTERY

DECLARATION OF DESIGN PERFORMANCE

TO THE REQUIREMENTS OF

RTCA DO-293 and IEC 60952-1

Applications: Fixed and Rotary Wing Aircraft, Fuselage Mounted

NOTE: Applications may not be a complete list of all applications for this battery type.

The data/information contained herein has been reviewed and approved for general release on the basis that this document contains no export-controlled information

Characteristic	RTCA DO-293 IEC 60952-1	Requirement/Performance	Test Report / Reference
Description	<p>The RG-400E/13 is a 24 volt, 13 ampere hour, valve regulated lead-acid aircraft storage battery.</p> <p>The RG-400E/13 battery consists of twelve 2 volt cells connected in series. The cells are enclosed by a one piece plastic monoblock container and a plastic one piece top which is secured to the monoblock with an epoxy cement. The monoblock and top are made of high-impact polypropylene. The monoblock is contained within a molded plastic outer container with a molded plastic cover which incorporates the hold down.</p> <p>The electrolyte is a sulfuric acid and water solution and is absorbed within the battery plates and separators. There is no free electrolyte. See Material Safety Data Sheet for hazardous material identification and precautions.</p>		
Format	IEC 60952-2	Concorde Drawing No. RG-400E/13	
Connector	IEC 60952-2	The battery is available with a Type Q terminal conforming to MS-3509.	
Mass		RG-400E/13 – 16.6 kg Max.	
Charging method	IEC 60952-1, 4.3	Constant potential at 28.25 V	
Any auxiliary requirement:		None	
Ventilation	DO-293, 1.9 IEC 60952-2	Battery is equipped with vent tubes	
Flammability	IEC 60952-2	RG-400E/13 outer container is flammable	
Spillability		Non spill	
Electrical Performance			
Rated Capacity (C1)	DO-293, 2.2.2 IEC 60952-1, 5.1.1	13 Ah	
Capacity at -18°C	DO-293, 2.2.3 IEC 60952-1, 5.1.2	6.5 Ah when discharged at the C1 rate.	
Capacity at -30°C	DO-293, 2.2.4 IEC 60952-1, 5.1.3	4.0 Ah when discharged at the C1 rate.	
Capacity at +50°C	DO-293, 2.2.5 IEC 60952-1, 5.1.4	14.5 Ah when discharged at the C1 rate.	
Power Rating +23°C	DO-293, 2.2.6.1 IEC 60952-1, 5.2.1.1	I _{pp} = 950 A, I _{pr} = 250 A	
Power Rating -18°C	DO-293, 2.2.6.2 IEC 60952-1, 5.2.1.2	I _{pp} = 615 A, I _{pr} = 125 A	
Power Rating -30°C	DO-293, 2.2.6.3 IEC 60952-1, 5.2.1.3	I _{pp} = 400 A, I _{pr} = 100 A	
Rapid Discharge Capacity at 23°C	DO-293, 2.3.1 IEC 60952-1, 5.3.1	6.3 Ah when discharged at 10 times the C1 rate to 10 volts.	

Characteristic	RTCA DO-293 IEC 60952-1	Requirement/Performance	Test Report / Reference
Rapid Discharge Capacity at -30°C	DO-293, 2.3.2 IEC 60952-1, 5.3.2	2.0 Ah when discharged at 10 times the C1 rate to 10 volts.	
Charge Retention	DO-293, 2.4 IEC 60952-1, 5.4	+23 C - Rating value for design = 80%	
		+50 C - Rating value for design = 75%	
Storage	DO-293, 2.5 IEC 60952-1, 5.5	DO-293 - 1 year storage life test in process	
Charge Stability	DO-293, 2.6 IEC 60952-1, 5.6, Class I	OK. Max battery temperature on charge = 51°C. Charge current fell during the charge period. Capacity at end of test > C1	
Short-circuit Current	DO-293, 2.7 IEC 60952-1, 5.7	Peak current = 1940A Last recorded current = 515A at 8.6s	
Charge Acceptance	DO-293, 2.8 IEC 60952-1, 5.8	+23 C = 100%	
		-18 C (battery with heaters only) N/A	
		-40 C (battery with heaters only) N/A	
Insulation Resistance	DO-293, 2.9.1 IEC 60952-1, 5.9.1	All samples successfully met the test requirement.	
Dielectric Strength	DO-293, 2.9.2 IEC 60952-1, 5.9.2	All samples successfully met the test requirement.	
Duty Cycle Performance	DO-293, 2.10 IEC 60952-1, 5.10	All samples successfully met the test requirement.	
Water Consumption Test	DO-293, 2.11 IEC 60952-1, 5.11	N/A	
Overcharge Endurance	DO-293, no requirement IEC 60952-1, 5.12	Not tested	
Cyclic Endurance	DO-293, 2.12 IEC 60952-1, 5.13	100 cycles	
Deep Discharge	DO-293, 2.13 IEC 60952-1, 5.14	All samples successfully met the test requirement.	
Induced Destructive Overcharge	DO-293, 2.14 IEC 60952-1, 5.15	All samples successfully met the test requirement.	
Electrical Emissions	DO-293, 2.15 IEC 60952-1, 5.16	N/A Battery contains no active electronics.	
Environmental Performance			
Vibration	DO-293, 3.1 IEC 60952-1, 6.1	Random vibration test per Curve C, section 8, DO-160E, 1 hour per axis.	R4088
Acceleration	DO-293, no requirement IEC 60952-1, 6.2	Not tested	

Characteristic	RTCA DO-293 IEC 60952-1	Requirement/Performance	Test Report / Reference
Operational Shock	DO-293, 3.3.1 IEC 60952-1, 6.3, Class I	Category B, DO-160E – OK	R4146
Crash Safety Shock	DO-293, 3.3.2 IEC 60952-1, 6.4	Category B, DO-160E, Category B, impulse and sustained – OK. Sustained per DO-160E Table 7-1, Aircraft type 5, Test type R, 20g's in each orientation.	R4146
Explosion Containment	DO-293, 3.4 IEC 60952-1, 6.5	All samples successfully met the test requirement.	
Altitude	DO-293, 3.5 IEC 60952-1, 6.6	Tested to 20621m (67654 ft) IAW DO-293.	
Rapid Decompression	DO-293, 3.5.2 IEC 60952 no reqmt	Tested from 2300m (8000 ft) to 20621m (67654 ft) IAW DO-293.	
Temperature Shock	DO-293, 3.6 IEC 60952-1, 6.7	RG-400E/13 tested from +85°C to -55°C IAW DO-293. Sample successfully met the test requirement.	
Fungus Resistance	DO-293, 3.7 IEC 60952-1, 6.8	DO-160E Category F. All samples successfully met the test requirement.	
Humidity	DO-293, 3.8 IEC 60952-1, 6.9	Qualified to DO-293 and DO-160E, Category B	

Characteristic	RTCA DO-293 IEC 60952-1	Requirement/Performance	Test Report / Reference
Fluid Contamination	DO-293, 3.9 IEC 60952-1, 6.10	<p>Test was performed on representative material samples. All samples successfully met the test requirement.</p> <p>Fluids tested:</p> <p>Fuels.</p> <ul style="list-style-type: none"> Aviation Jet A fuel Aviation piston engine fuel (100LL AVGAS) <p>Hydraulic fluids</p> <ul style="list-style-type: none"> Mineral based (MIL-H-5606) Non-mineral based synthetic (MIL-PRF-83282 and MIL-PRF-87257) <p>Lubricating oils</p> <ul style="list-style-type: none"> Mineral based (MIL-L-6081) Ester based synthetic (MIL-L-23699) Internal combustion engine SAE 15W40 <p>Solvents and cleaning fluids</p> <ul style="list-style-type: none"> Isopropyl alcohol (TT-I-735) Denatured alcohol <p>De-icing fluid</p> <ul style="list-style-type: none"> Ethylene Glycol Propylene Glycol AMS 1424 (SAE AEA Type I) AMS 1428 (SAE AEA Type VI) <p>Insecticides - none</p> <p>Sullage - none</p> <p>Disinfectants (heavy duty phenolics) - none</p> <p>Coolant dielectric fluid - none</p> <p>Fire extinguishants - none</p>	CB020107-1 27363-0716526
Salt Spray	DO-293, 3.10 IEC 60952-1, 6.11	Qualified to DO-293 and DO-160E, Category S.	13489
Physical Integrity at High Temperature	DO-293, 3.11 IEC 60952-1, 6.12	All samples successfully met the test requirement.	
Flammability	DO-293, no requirement IEC 60952-1, 6.13	Not tested. See Section 1	
Electrolyte Resistance	DO-293, 3.12 IEC 60952-1, 6.14	All samples successfully met the test requirement.	
Thermal Sensors	DO-293, 3.13 IEC 60952-1, 6.15	N/A	
Component Qualification tests	DO-293, 3.14 IEC 60952-1, 6.16	All samples successfully met the test requirement.	
Battery Airtightness	DO-293, no requirement IEC 60952-1, 6.17	N/A	

Characteristic	RTCA DO-293 IEC 60952-1	Requirement/Performance	Test Report / Reference
Cell Baffle	DO-293, no requirement IEC 60952-1, 6.18	N/A. Applies only to nickel-cadmium batteries only.	
Strength of Receptacle	DO-293, 3.15 IEC 60952-1, 6.19	All samples successfully met the test requirement.	
Handle Strength	DO-293, 3.16 IEC 60952-1, 6.20	N/A	

N/A = Not Applicable

Authentication:

Manufacturer. **Concorde Battery Corporation**

Signed:
Name of signatory: **John B. Timmons, PE**
Title or Function: **Vice President Engineering**