





NOTES: UNLESS OTHERWISE SPECIFIED

1. SEE DRAWING NO. CB-00400 AND PROCEDURE P-1000 FOR ASSEMBLY AND TEST INSTRUCTIONS. PROCEDURES AND ASSEMBLY DRAWING ARE FOR INTERNAL USE ONLY.
2. ALL TESTING IS PERFORMED IAW BATTERY COUNCIL INTERNATIONAL STANDARDS.
3. ALL DIMENSIONS ARE IN INCHES [MILLIMETERS].
4. ABBREVIATION USED IN TITLE IS: SEALED LEAD ACID (SLA).

REVISIONS			
REV	DESCRIPTION	DATE	APPROVED
A	REVISED WEIGHT, 91 LBS [41.3 KG] WAS 97 LBS [44.0 KG]	12/4/12	JBT
B	REDESIGNED COVER	12/20/17	PH



ISOMETRIC VIEW



ENVELOPE DRAWING

CAPACITY RATINGS	
PART NUMBER	PVX-1530T
NOMINAL WEIGHT	91 LBS [41.3 KG]
AMPERE HOUR CAPACITY @ 24 HOUR 1.75 VOLTS/CELL @ 77°F (25°C)	153 AH

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCES ARE:			CONTRACT NO.		CONCORDE BATTERY CORPORATION 2009 SAN BERNARDINO RD, W. COVINA, CA 91790			
FRACTIONS	DECIMALS	ANGLES	APPROVALS	DATE	TITLE			
±1/32	.XX ± .12 .XXX ± .060	±1°	DRAWN	6/30/09	BATTERY, SLA, 12 VOLT, PVX-1530T			
TREATMENT	NONE		CHECKED	7/13/09	SIZE	CAGE CODE	DWG NO.	REV
FINISH	NONE		APPROVED	7/14/09	C	63017	PVX-1530T	B
SIMILAR TO	CALC WT		ISSUED	12/21/17	SCALE	1:3		SHEET 1 OF 1